



Automatic Cleaning Module (ACM)

For TU5300sc/TU5400sc

The ACM ensures your TU5 sample vial is free of contamination that may interfere with your low-level turbidity measurements. Let Hach Service keep your ACM maintained properly and on schedule to avoid measurement errors and the need for manual cleaning.

Benefits of Service

- Ensures peak performance to protect TU5 turbidity measurements against vial contamination
- Detects and prevents issues that can degrade performance or reduce instrument life
- Eliminates time and hassle of performing service and managing maintenance schedules
- Technical support hotline provides rapid and direct resolution and field support when an immediate fix is not possible

Annual Average Maintenance Time: Up to 1 hour
Recommended Maintenance Frequency: 1x / year

Essential Maintenance Tasks Performed

Routine:

- Perform visual inspection
- Clean device exterior
- Replace wiper to ensure optimal cleaning

Advanced:

- Verify and ensure proper operation
- Resolve any error or warning messages that may impact functionality
- Produce service report and performance certificate

Parts Replaced During Maintenance

Part #	Description	Qty.	Frequency
LZY915 LZQ176	Silicone wiper or Fiber wiper	1	12 months

This part and replacement labor are included with a Hach Service Plan at the recommended frequency. Service Plan for the associated TU5300sc/TU5400sc must also be purchased separately. Coverage is available for repairs on site or at the Hach Service Center.

For more information, visit: www.hach.com/service

World Headquarters: Loveland, Colorado USA | hach.com

United States 800-227-4224 fax: 970-669-2932 email: orders@hach.com
Outside United States 970-669-3050 fax: 970-461-3939 email: int@hach.com

©Hach Company, 2024. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.

DOC063.53.38073.Nov24