

Corning Incorporated
Life Sciences

Registered
ISO 9001:2008

Product Description

Catalog Number: 1395-100

Product Description: PYREX® Bottle, Media, Storage, GL-45 Thread, 100 mL,
with Orange PP Screw Cap and PP Drip Ring

Component Materials:

Glass - Type I Class A - Low-Expansion Borosilicate Glass,
per ASTM E-438 (Standard Specification for Glasses in Laboratory Apparatus)
Cap - Polypropylene (PP)
Ring - Polypropylene (PP)

Attributes:

Capacity - 100 mL Approximate
Product Dimensions - 56 mm Body OD x 100 mm High (w/o cap), 30 mm Neck ID

Autoclaving:

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for for 15 minutes.

Heating / Cooling:

The normal use temperature range for this product is from -50°C to +125°C. The upper temperature limit for the plastic components of this product is 140°C. This product is not designed for direct contact heating.

Vacuum / Pressure:

This product is not designed for and is not rated for vacuum or pressure applications.

Sterilization:

Shipped Not Sterile

TSE/BSE:

This product complies with the latest revision of EMEA/410/01, *Note for Guidance on Minimizing the Risk of Transmitting Animal Spongiform Encephalopathy Agents via Human and Veterinary Medicinal Product* by virtue that any component of the product which may include material of bovine origin has been processed per the specific conditions of section 6.4 of EMEA/410/01.

Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Revision Date:

17 JUN 2013

Rev No: 1