Corning Incorporated
Life Sciences

Registered
ISO 9001:2008

Product Description

Catalog Number: 2105-25

Product Description: PYREX® Buret, Serialized/Certified Class A, Colored Scale, 25 mL with 2 mm Straight Bore PTFE Stopcock Plug and LDPE Dust Cover

Component Materials:
Glass - Type I Class A - Low-Expansion Borosilicate Glass, per ASTM E438 (Standard Specification for Glasses in Laboratory Apparatus)
Plug - Polytetrafluoroethylene (PTFE)
Cover - Low Density Polyethylene (LDPE)

Attributes:
ASTM Reference - E287 (Specification for Laboratory Glass Graduated Burets)
E694 (Specification for Volumetric Ware)
E542 (Specification for Calibration of Laboratory Volumetric Apparatus)
Capacity - 25 mL; Tolerance: ±0.03 mL at any mark
Product Dimensions - 12 mm OD x 560 mm High

Autoclaving:
This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for 15 minutes.

Heating / Cooling:
This product is designed for volumetric measurement and therefore typical use will be at standard room temperature. Volumetric glassware should not be subjected to temperatures in excess of 150°C.

Vacuum / Pressure:
This product is not designed for and is not rated for vacuum or pressure applications.

Sterilization:
Shipped Not Sterile

Lot Number Designation:
Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Revision Date:
18 JUN 2013

Rev No: 1