

Corning Incorporated  
Life Sciences

Registered  
ISO 9001:2008

## Product Description

**Catalog Number:** 1395-50

**Product Description:** PYREX® Bottle, Media, Storage, GL-32 Thread, 50 mL,  
with Orange PP Screw Cap and PP Drip Ring

**Component Materials:**

Glass - Type I Class A - Low-Expansion Borosilicate Glass,  
per ASTM E-438 (Standard Specification for Glasses in Laboratory Apparatus)  
Cap - Polypropylene (PP)  
Ring - Polypropylene (PP)

**Attributes:**

Capacity - 50 mL Approximate  
Product Dimensions - 46 mm Body OD x 88 mm High (w/o cap), 17 mm Neck ID

**Autoclaving:**

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for for 15 minutes.

**Heating / Cooling:**

The normal use temperature range for this product is from -50°C to +125°C. The upper temperature limit for the plastic components of this product is 140°C. This product is not designed for direct contact heating.

**Vacuum / Pressure:**

This product is not designed for and is not rated for vacuum or pressure applications.

**Sterilization:**

Shipped Not Sterile

**TSE/BSE:**

This product complies with the latest revision of EMEA/410/01, *Note for Guidance on Minimizing the Risk of Transmitting Animal Spongiform Encephalopathy Agents via Human and Veterinary Medicinal Product* by virtue that any component of the product which may include material of bovine origin has been processed per the specific conditions of section 6.4 of EMEA/410/01.

**Lot Number Designation:**

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

**Revision Date:**

17 JUN 2013

Rev No: 1