

Corning Incorporated Life Sciences Product Description



Catalog Number: 5340-2L

Product Description: PYREX® Flask, Filtering, Heavy Wall, Graduated, Tubulated, 2000 mL Tooled for Rubber Stopper #9

Component Materials:

Type I Class A - Low-Expansion Borosilicate Glass, per ASTM E438 (Standard Specification for Glasses in Laboratory Apparatus)

Attributes:

Capacity - 2000 mL ± 100 mL at any mark (5% of full capacity)
Product Dimensions - 168 mm OD x 292 mm High
Tubulation - 13 mm OD

Autoclaving:

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for 15 minutes.

Heating and Cooling:

This product should NOT be heated while being used in a Vacuum or Pressure application as the combination of thermal and mechanical stresses could cause a failure.

This product is not designed for freezing applications.

Vacuum / Pressure:

This product is designed for full vacuum of 760 mmHg (15 psi negative pressure).

This product is not designed for and is not rated for pressure applications.

Sterilization:

Shipped Not Sterile.

TSE/BSE:

Materials of animal origin are not used in the manufacture of this product.

Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Certifications:

ISO 9001

To get Certificates per Lot and Serialized PYREX® items, visit www.corning.com/resources.

Corning Glassware page:



Enter item ID and serial or lot number of your PYREX product.

