## Corning Incorporated Life Sciences

Registered ISO 9001:2008

# **Product Description**

Catalog Number: 5580-200

Product Description: PYREX® Flask, Volumetric, Class A, 200 mL

with LDPE Snap Cap

**Component Materials:** 

Glass - Type I Class A - Low-Expansion Borosilicate Glass,

per ASTM E438 (Standard Specification for Glasses in Laboratory Apparatus)

Cap - Low Density Polyethylene (LDPE)

Attributes:

ASTM Reference - E288 (Specification for Volumetric Flasks)

E694 (Specification for Volumetric Ware)

E542 (Specification for Calibration of Laboratory Volumetric Apparatus)

Capacity - 200 mL ±0.10 mL

Product Dimensions - 74 mm OD x 214 mm High without Cap

Autoclaving:

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for 15 minutes.

Heating / Cooling:

This product is designed for volumetric measurement and therefore typical use will be at standard room temperature. Volumetric glassware should not be subjected to temperatures in excess of 150°C.

#### Vacuum / Pressure:

This product is not designed for and is not rated for vacuum or pressure applications.

### Sterilization:

Shipped Not Sterile

Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

#### **Revision Date:**

19 JUL 2013

Rev No: 1