

Corning Incorporated Life Sciences Product Description



Catalog Number: 1395-3X

Product Description: PYREX® Bottle, Media, Storage, GL-45 Thread, 3500 mL, with Orange PP Screw Cap and PP Drip Ring

Component Materials:

Glass - Type I Class A - Low-Expansion Borosilicate Glass, per ASTM E438 (Standard Specification for Glasses in Laboratory Apparatus)

Cap - Polypropylene (PP)

Ring - Polypropylene (PP)

Attributes:

Capacity - 3500 mL Approximate

Product Dimensions - 166 mm Body OD x 295 mm High (w/o cap), 30 mm Neck ID

Autoclaving:

This product will withstand repeated standard autoclave cycles of 121°C at 15 psi for 15 minutes.

Heating and Cooling:

The normal use temperature range for this product is from -50°C to +125°C. The upper temperature limit for the plastic components of this product is 140°C. This product is not designed for direct contact heating.

Vacuum / Pressure:

This product is a component part and not specifically rated for vacuum or pressure.

Sterilization:

NA

TSE/BSE:

This product complies with the latest revision of EMEA/410/01. Note for Guidance on Minimizing the Risk of Transmitting Animal Spongiform Encephalopathy Agents via Human and Veterinary Medicinal Product by virtue that any component of the product which may include material of bovine origin has been processed per the specific conditions of section 6.4 of EMEA/410/01.

Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Certifications:

ISO 9001

To get Certificates per Lot and Serialized PYREX® items, visit www.corning.com/resources.

Corning Glassware page:



Enter item ID and serial or lot number of your PYREX product.

